

## SAFETY DATA SHEET

### Stuk Sprayline Linemarker Green Aerosol

#### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME Stuk Sprayline Linemarker Green Aerosol  
 PRODUCT NO. SA1669  
 SUPPLIER STUK Ltd  
 3 Empire Way  
 Gloucester  
 GL2 5HY  
 01452 505 712  
 01452 303 700

#### 2 HAZARDS IDENTIFICATION

Extremely flammable Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness. Irritating to eyes. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION (1999/45) Xi;R36. F+;R12. R52/53, R66, R67.

##### ENVIRONMENT

The product contains a substance which is harmful to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

##### PHYSICAL AND CHEMICAL HAZARDS

Pressurised container: Must not be exposed to temperatures above 50°C. The product is extremely flammable, and explosive vapour/air mixtures may be formed even at normal room temperatures.

##### HUMAN HEALTH

In high concentrations, vapours and spray mists are narcotic and may cause headache, fatigue, dizziness and nausea.

#### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content %	Classification (67/548/EEC)
ACETONE	200-662-2	67-64-1	10-30%	F;R11 Xi;R36 R66 R67
BUTANE/ISOBUTANE		106-97-8	10-30%	F+;R12.
BUTYL ACETATE -norm	204-658-1	123-86-4	5-10%	R10 R66 R67
PROPANE	200-827-9	74-98-6	10-30%	F+;R12
SOLVENT NAPHTHA, LIGHT AROMATIC	265-199-0	64742-95-6	10-30%	Xn;R65. Xi;R37. N;R51/53. R10,R66,R67.

The Full Text for all R-Phrases is Displayed in Section 16

#### 4 FIRST-AID MEASURES

##### GENERAL INFORMATION

Move the exposed person to fresh air at once.

##### INHALATION

Move the exposed person to fresh air at once. Perform artificial respiration if breathing has stopped. Keep the affected person warm and at rest. Get prompt medical attention.

##### INGESTION

Immediately rinse mouth and provide fresh air. Do not induce vomiting. Get medical attention if any discomfort continues.

##### SKIN CONTACT

Wash skin with soap and water. Get medical attention if any discomfort continues.

##### EYE CONTACT

Immediately rinse with water. Continue to rinse for at least 15 minutes. Make sure to remove any contact lenses from the eyes before rinsing. Get medical attention promptly if symptoms occur after washing.

## Stuk Sprayline Linemarker Green Aerosol

### 5 FIRE-FIGHTING MEASURES

#### EXTINGUISHING MEDIA

Water spray, foam, dry powder or carbon dioxide.

#### SPECIAL FIRE FIGHTING PROCEDURES

Use water spray to reduce vapours. Aerosol cans may explode in a fire. Cool aerosol containers exposed to heat with water spray and remove container, if no risk is involved.

#### UNUSUAL FIRE & EXPLOSION HAZARDS

Extremely flammable. Forms explosive mixtures with air. May explode in a fire. Vapours are heavier than air and may spread near ground to sources of ignition.

#### SPECIFIC HAZARDS

Pressurised container: Must not be exposed to temperatures above 50°C.

### 6 ACCIDENTAL RELEASE MEASURES

#### PERSONAL PRECAUTIONS

Ensure suitable personal protection (including respiratory protection) during removal of spillages in a confined area.

#### ENVIRONMENTAL PRECAUTIONS

Avoid discharge into drains.

#### SPILL CLEAN UP METHODS

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb in vermiculite, dry sand or earth and place into containers. Provide ventilation and confine spill. Do not allow runoff to sewer.

### 7 HANDLING AND STORAGE

#### USAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Read and follow manufacturer's recommendations. Avoid inhalation of vapours and spray mists. Do not spray on a naked flame or any incandescent material. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited.

#### STORAGE PRECAUTIONS

Extremely flammable. Store at moderate temperatures in dry, well ventilated area. Keep away from heat, sparks and open flame. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

### 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
ACETONE	WEL	500 ppm	1210 mg/m <sup>3</sup>	1500 ppm	3620 mg/m <sup>3</sup>	
BUTANE/ISOBUTANE	WEL	600 ppm		750 ppm		
BUTYL ACETATE -norm	WEL	150 ppm	724 mg/m <sup>3</sup>	200 ppm	966 mg/m <sup>3</sup>	
SOLVENT NAPHTHA, LIGHT AROMATIC	WEL	25 ppm	50 mg/m <sup>3</sup> (Sk)			

WEL = Workplace Exposure Limit.

#### RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit. In case of inadequate ventilation use suitable respirator.

#### HAND PROTECTION

For prolonged or repeated skin contact use suitable protective gloves.

#### EYE PROTECTION

Wear approved chemical safety goggles where eye exposure is reasonably probable.

#### HYGIENE MEASURES

When using do not eat, drink or smoke. Wash promptly if skin becomes wet or contaminated.

### 9 PHYSICAL AND CHEMICAL PROPERTIES

**Stuk Sprayline Linemarker Green Aerosol**

APPEARANCE	Aerosol.
COLOUR	Varying.
ODOUR	of solvents
PHYSICAL DATA COMMENTS	Information given concerns the major ingredient. 23 Flammable gas.
FLASH POINT (°C)	<-40°C
AUTO IGNITION	410-580
TEMPERATURE (°C)	
FLAMMABILITY LIMIT - LOWER(%)	1.8%
FLAMMABILITY LIMIT - UPPER(%)	9.5%

**10 STABILITY AND REACTIVITY**

## STABILITY

Highly volatile.

## CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition. Avoid exposure to high temperatures or direct sunlight.

**11 TOXICOLOGICAL INFORMATION**

## SKIN CONTACT

Skin irritation is not anticipated when used normally. Repeated exposure may cause skin dryness or cracking.

## EYE CONTACT

Irritating to eyes. Spray and vapour in the eyes may cause irritation and smarting.

## HEALTH WARNINGS

In high concentrations, vapours are narcotic and may cause headache, fatigue, dizziness and nausea. Arrhythmia, (deviation from normal heart beat).

## ROUTE OF ENTRY

Inhalation.

## TARGET ORGANS

Central nervous system Respiratory system, lungs

## MEDICAL SYMPTOMS

Narcotic effect. Vapours may cause drowsiness and dizziness.

**12 ECOLOGICAL INFORMATION**

## ECOTOXICITY

The product contains a substance which is harmful to aquatic organisms and which may cause long term adverse effects in the aquatic environment. Dangerous for the environment if discharged into watercourses. Do not allow to enter drains, sewers or watercourses.

**13 DISPOSAL CONSIDERATIONS**

## DISPOSAL METHODS

Make sure containers are empty before discarding (explosion risk). Do not puncture or incinerate even when empty. Dispose of waste and residues in accordance with local authority requirements.

**14 TRANSPORT INFORMATION**

PROPER SHIPPING NAME

AEROSOLS

**Stuk Sprayline Linemarker Green Aerosol**

ENVIRONMENTALLY HAZARDOUS SUBSTANCE/MARINE POLLUTANT	No.
UN NO. ROAD	1950
ADR CLASS NO.	2, 5F
ADR CLASS	Class 2: Gases
ADR PACK GROUP	#
ADR LABEL NO.	2.1
UN NO. SEA	1950
IMDG CLASS	2
IMDG PACK GR.	#
EMS	F-D, S-U
UN NO. AIR	1950
AIR CLASS	2
AIR SUB CLASS	2.1
AIR PACK GR.	#

**15 REGULATORY INFORMATION**

## LABELLING



Irritant



Extremely flammable

## CONTAINS

SOLVENT NAPHTHA, LIGHT AROMATIC

## RISK PHRASES

R12	Extremely flammable.
R36	Irritating to eyes.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

## SAFETY PHRASES

S2	Keep out of the reach of children.
S9	Keep container in a well-ventilated place.
S16	Keep away from sources of ignition - No smoking.
S23	Do not breathe vapour/spray.
S25	Avoid contact with eyes.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S37	Wear suitable gloves.
S51	Use only in well-ventilated areas.
S56	Dispose of this material and its container to hazardous or special waste collection point.

## UK REGULATORY REFERENCES

Health and Safety at Work Act 1974. Chemicals (Hazard Information & Packaging) Regulations. The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments.

## EU DIRECTIVES

Dangerous Preparations Directive 1999/45/EC.

## STATUTORY INSTRUMENTS

Control of Substances Hazardous to Health.

**Stuk Sprayline Linemarker Green Aerosol**

APPROVED CODE OF PRACTICE

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

**16 OTHER INFORMATION**

DATE	21 September 2011
RISK PHRASES IN FULL	
R12	Extremely flammable.
R10	Flammable.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
R11	Highly flammable
R36	Irritating to eyes.
R37	Irritating to respiratory system.
R66	Repeated exposure may cause skin dryness or cracking.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R67	Vapours may cause drowsiness and dizziness.

## DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.